

# SIVGE T10&T20 SERIES


## Mobile Elevating Work Platforms



Product conform with below standards:

- 2006/42/EC Machinery Directive
- EN 280-2013+A1-2015
- EN ISO 12100: 2010
- EN 60204-1:2006+A1:2009+AC:2010
- EN ISO 13849-1:2015
- GB25949-2010
- JB/T12216-2015

- \* Suitable for 1 or 2 person to work upraised.
- \* Maximum working height available: 8m, 10m, 12m
- \* Power supply available: DC 12 or 24V



HANGZHOU SIVGE MACHINERY CO.,LTD  
ADD: NO 15 KANGXIAN ROAD, GONGSHU DISTRICT,  
HANGZHOU, ZHEJIANG, CHINA  
POST CODE: 310015 TEL: +86 571 88043728 88043711  
FAX: +86 571 88043715 E-mail: info@sivge.com

© [www.sivge.com](http://www.sivge.com)  
© [www.aerial-workplatform.com](http://www.aerial-workplatform.com)  
sivge stock(833084)

# Trailer type Mobile Elevating Work Platforms

## STANDARD FEATURES:

- Dual controls operation
- Compact size with easy quick guardrail assemblage
- Easily towed behind pickup or cars
- Emergency stop buttons at both controls
- Emergency lowering device in case of power supply failure
- Maintenance-free battery with intelligent charger
- Low maintenance requirements will save you time and money

	T1006	T1008	T2008	T2010
Model-code	GTWT6-1006	GTWT8-1008	GTWT8-2008	GTWT10-2010
Platform height(m)(h <sub>1</sub> )	6	8	8	10
Working height(m)(h <sub>2</sub> )	8	10	10	12
Capacity(kg)/occupants	160/1	136/1	200/2	200/2
Platform size(mm)	650*630	650*630	1200*600	1200*600
Outrigger footprint(mm)	2430*2280	2430*2280	2480*2420	2480*2420
Stowed length(mm)(l <sub>0</sub> )	2200	2200	2590	2590
Stowed width(mm)(w <sub>0</sub> )	1100	1100	1100	1100
Stowed height(mm)(h <sub>0</sub> )	1890	2200	2230	2230
Machine weight(kg)	480	520	800	870
Moving methods	Trailer type	Trailer type	Trailer type	Trailer type
Power supply	DC12V	DC12V	DC24V	DC24V
Tire size				
Power input(kw)	0.7	0.7	1.2	1.2
Battery	12V/120Ah	12V/120Ah	12V/120Ah*2	12V/120Ah*2
Max. allowed wind speed	12.5m/s	12.5m/s	12.5m/s	12.5m/s
Rated oil pressure	12Mpa	12Mpa	12Mpa	12Mpa

※ Optional: design service is available if the standard models cannot fulfill the needs.

